

CODE SECTION	SCOPE OF CODE CHANGE	CODE CHANGE YEAR	MODIFICATION TO ADOPTION	NOTES REQUIRED ON PLANS	DETAILS REQUIRED ON PLANS	MISC. NOTES
102.4	CLARIFIES REFERENCE STANDARDS	2012	CLARIFICATION			
102.4.1	CHANGES WORDING TO "CONFLICTS"	2012	CLARIFICATION			
102.4.2	CLARIFIES CODES TAKING PRECEDENCE	2012	CLARIFICATION			
104.10	EXPANDS ON GRANTING MODIFICATIONS	2012	MODIFICATION			
104.10.1	FLOOD HAZARD AREA MODIFICATIONS	2012	ADDITON			
105.2	FENCE HT. EXEMPT TO 7 FEET		MODIFICATION			
107.1	EXPANDS ON SUBMITTAL DOCUMENTS	2009	CLARIFICATION			
202	DEFINITIONS: CONGREGATE LIVING FACILITIES, DELETES "SEE SECTION 310.2"	2012	CLARIFICATION			
202	HIGH-RISE BLDG REDEFINED	2009	CLARIFICATION			
202	STORY ABOVE GRADE PLANE REDEFINED	2009	CLARIFICATION			
303.1	CLARIFIES ACCESSORY ASSEMBLY SPACES IN 'E' OCCUPANCIES	2012	CLARIFICATION			
303.1.1	CLARIFIES ACCESSORY SPACES IN SMALL BLDGS & TENANT SPACES	2012	CLARIFICATION			
303.1.2	CLARIFIES ACCESSORY SPACES IN SMALL ASSEMBLY SPACES	2012	CLARIFICATION			
303.1.3	CLARIFIES ACCESSORY SPACES ASSOCIATED WITH GROUP 'E' OCCUPANCIES	2012	CLARIFICATION			
303.1.4	CLARIFIES ACCESSORY SPACES TO RELIGIOUS WORSHIP	2012	CLARIFICATION			

303.3	CASINO GAMING FLOOR IDENTIFIED AS A-2	2012	ADDITION			
303.3	ASSEMBLY GROUP A-2 USES EXPANDED	2012	ADDITION			
304.1	BUSINESS GROUP 'B' DEFINITION EXPANDED	2009	ADDITION			
304.1.1	CLINIC-OUTPATIENT REDEFINED	2009	ADDITION			
202	AMBULATORY HEALTH CARE FACILITY REDEFINED	2009	ADDITION			
306.2	MODERATE-HAZARD F-1 EXPANDED	2012	CLARIFICATION			
307.1(1)	NOTES ADDED TO TABLE 307.1(1); 307.4	2012	MODIFICATION			
307.4	HIGH-HAZARD GROUP H-2, EXPANDED COMBUSTIBLE DUST WORDING	2012	MODIFICATION			
308.2	DEFIITIONS: NEW DEFINITIONS RELATED TO HEALTH CARE FACILITIES	2012	CLARIFICATION			
308.4	INSTITUTIONAL GROUP I-2 CLASSIFICATION APPLICABILITY	2012	MODIFICATION			
308.4.1	FIVE OR FEWER PERSONS RECEIVING CARE, WORDING CHANGED	2012	MODIFICATION			
308.5.1	ADULT CARE FACILITY NOW I-4 OCCUPANCY CLASSIFICATION	2009	MODIFICATION			
310.1	RESIDENTIAL GROUP 'R', ADDITIONS TO R-1, R-2 & R-4.	2009	ADDITION			
310.6	MODIFICATION: ALLOWANCE FOR CONSTRUCTING R-4 SUPERVISED RESIDENTIAL CARE FACILITY UNDER IRC ELIMINATED	2012	MODIFICATION			
402.1	APPLICABILITY: CLARIFICATIONS TO OPEN MALL BUILDINGS	2012	CLARIFICATION			
402.2	DEFINITIONS: COVERED & OPEN MALL BUILDINGS	2009	ADDITION			
402.5.2	CHANGES MINIMUM FLOOR AND ROOF OPENING WIDTH ABOVE GRADE	2009	ADDITION			
402.6.1	PERMANENT OPEN SPACE REDUCTION FOR COVERED MALL	2009	MODIFICATION			
402.8	CHANGES INTERIOR WALL & CEILING	2009	MODIFICATION			

	FINISHES WITHIN MALLS & EXITS					
403.4.4	ADDITION: HIGH-RISE BUILDINGS NOW REQUIRE EMERGENCY RESPONDER RADIO COVERAGE	2009	ADDITION			
403.4.6	ADDITION: NATURAL OR MECHANICAL MEANS OF SMOKE REMOVAL IN HIGH-RISE BLDGS NOW REQUIRED	2009	ADDITION			
403.5.2	ADDITION: ANOTHER EXIT STAIRWAY REQUIRED IN HIGH-RISE BLDGS.	2009	ADDITION			
403.5.5	ADDITION: HIGH-RISE BUILDINGS LUMINOUS EGRESS MARKINGS	2009	ADDITION			
403.6.1	MODIFICATION: HIGH-RISE BUILDINGS FIRE ACCESS ELEVATORS INCREASED IN NUMBERS	2012	MODIFICATION			
403.6.1	ADDITION: FIRE SERVICE ACCESS ELEVATOR REQUIRED IN HIGH-RISE BUILDINGS	2009	ADDITION			
403.6.2	HIGH-RISE ELEVATORS CAN NOW BE USED FOR OCCUPANT SELF-EVACUATION	2009	ADDITION			
406.2.4	PARKING GARAGE VEHICLE BARRIER HEIGHT INCREASED TO 33 INCHES	2009	MODIFICATION			
406.4	PRIVATE PARKING STRUCTURES OUTSIDE SEC. 406.3 NOW I.D.'d AS PUBLIC PARKING GARAGES	2012	CLARIFICATION			
406.5.2.1	OPEN PARKING GARAGES-OPENINGS BELOW GRADE	2012	ADDITION			
406.5.5	OPEN PARKING GARAGES-HEIGHT & AREA INCREASES	2012	MODIFICATION			
408.7	SECURITY GLAZING IN GROUP I-3 OCCUPANCIES	2009	MODIFICATION			
410.3.5	STAGE PROSCENIUM CURTAIN. DELETED SEC. 410.3.5.1, 410.3.5.2, 410.3.5.3 & 410.3.5.4	2009	MODIFICATION			
410.6.3	OUTDATED TERMINOLOGY REPLACED WITH "TECHNICAL PRODUCTION AREA"	2012	CLARIFICATION			

410.6.3, 202	TECHNICAL PRODUCTION AREA DEFINES	2012	CLARIFICATION			
410.6.3.1	MEANS OF EGRESS	2012	CLARIFICATION			
410.6.3.2	TRAVEL DISTANCE	2012	CLARIFICATION			
410.6.3.3	TWO MEANS OF EGRESS	2012	CLARIFICATION			
410.6.3.4	PATH OF EGRESS TRAVEL	2012	CLARIFICATION			
410.6.3.5	WIDTH-PATH OF EGRESS IN TECHNICAL PRODUCTION AREAS	2012	CLARIFICATION			
412.4.6.2	ANCILLARY AIRCRAFT SPACES NO LONGER INCLUDED IN FIRE AREA SIZE FOR FIRE SUPPRESSION REQUIREMENTS	2012	MODIFICATION			
414.5	INSIDE STORAGE, DISPENSING, AND USE OF HAZARDOUS MATERIALS. SCOPING	2012	CLARIFICATION			
419, 202	LIVE/WORK UNITS	2012	MODIFICATION			
419.1	LIVE/WORK UNITS, GENERAL	2009	ADDITION			
419.1.1	LIVE/WORK UNITS, LIMITATIONS	2009				
419.2	OCCUPANCIES	2012	MODIFICATIONS			
419.2	OCCUPANCIES	2009	ADDITION			
419.3, 3.1,3.2,3.3,3.4	MEANS OR EGRESS, EGRESS CAPACITY, SLIDING DOORS, SPIRAL STAIRWAYS, LOCKS	2012	MODIFICATION			
419.3, 3.1,3.2,3.3,3.4	MEANS OF EGRESS, EGRESS CAPACITY, SLIDING DOORS, SPIRAL STAIRS, LOCKS	2009	ADDITION			
419.4,5,6,7,8,9	VERTICAL OPENINGS, FIRE PROTECTION, STRUCTURAL, ACCESSIBILITY, VENTILATION, PLUMBING FACILITIES	2012	MODIFICATIONS			
419.4, 5,6,7,8	VERTICAL OPENINGS, FIRE PROTECTION, STRUCTURAL, ACCESSIBILITY, VENTILATION	2009	ADDITIONS			
420.2	FIRE SEPARATION WALLS OF DWELLING/SLEEPING UNITS EXPANDED	2009	ADDITION			
420.3	HORIZONTAL SEPARATION	2009	ADDITION			
422.2	AMBULATORY CARE FACILITIES,	2012	MODIFICATION			

	SEPARATION FROM NONRELATED USES					
422.2	SMOKE BARRIERS	2009				
422.3	SMOKE COMPARTMENTS	2012	MODIFICATION			
422.3	REFUGE AREA	2009	ADDITION			
422.4	REFUGE AREA	2012	MODIFICATION			
422.4	INDEPENDENT EGRESS	2009	ADDITION			
422.5	INDEPENDENT EGRESS	2012	MODIFICATION			
422.5	AUTOMATIC SPRINKLER SYSTEMS	2009	ADDITION			
422.6	AUTOMATIC SPRINKLER SYSTEM	2012	MODIFICATION			
422.6	FIRE ALARM SYSTEMS	2009	MODIFICATION			
422.7	FIRE ALARM SYSTEM	2012	MODIFICATION			
423.1, 423.1.1,	STORM SHELTERS, GENERAL AND SCOPE	2009	ADDITION			
423.2	DEFINITIONS: STORM SHELTER, COMMUNITY STORM SHELTER, RESIDENTIAL STORM SHELTER	2009	ADDITION			
424.1	CHILDREN'S PLAY STRUCTURES, NOW INCLUDES ANY LOCATION	2012	MODIFICATION			
424.2	MATERIALS, NONCOMBUSTIBLE & COMBUSTIBLE	2012	MODIFICATION			
424.3	FIRE PROTECTION, LEVEL OF FIRE SUPPRESSION AND DETECTION	2012	MODIFICATION			
424.4	SEPARATION, HORIZONTAL	2012	MODIFICATION			
424.5	AREA LIMITS, NOT GREATER THAN 300 SQ. FT., UNLESS APPROVED	2012	MODIFICATION			
501.2	ADDRESS IDENTIFICATION, MULTIPLE LOCATIONS IF REQUIRED BY FIRE DEPT.	2012	MODIFICATION			
502.1	BASEMENT DEFINITION REVISED	2009	MODIFICATION			
TABLE 503	REDUCTION IN ALLOWABLE BLDG. HEIGHT	2009	MODIFICATION			
505.2.2	MEZZANINE MEANS OF EGRESS, NOW REFERENCES CHAPTER 10	2012	MODIFICATION			
506.2.1	FRONTAGE INCREASE FOR BUILDINGS ON THE SAME LOT	2009	CLARIFICATION			
506.2	ALLOWABLE AREA FRONTAGE INCREASE	2012	CLARIFICATION			

506.5	METHOD OF CALCULATING ALLOWABLE AREA FOR MULTI-STORY BUILDINGS	2009	CLARIFICATION			
507.1	OCCUPANCY GROUPS NOT SPECIFIED UNDER UNLIMITED AREA BUILDING PROVISIONS NOW UNDER ACCESSORY OCCUPANCIES PROVISIONS	2012	CLARIFICATION			
507.1	OPEN SPACE WIDTH FOR UNLIMITED AREA BUILDINGS	2012	CLARIFICATION			
507.6 507.7	GROUP A-3 OCCUPANCIES OF TYPE III & IV CONSTRUCTION UNLIMITED IN AREA WITH CERTAIN CONDITIONS	2009	MODIFICATION			
507.8	LIMITATIONS ON GROUP 'H' UNLIMITED AREA BUILDINGS	2012	CLARIFICATION			
508.2.5	INCIDENTAL ACCESSORY OCCUPANCIES NOW HAVE SIZE LIMITATIONS	2009	MODIFICATION			
TABLE 508.2.5	PARKING GARAGES & STORAGE ROOMS NO LONGER INCIDENTAL ACCESSORY OCCUPANCIES	2009	MODIFICATION			
TABLE 508.4	GROUP I-2 SEPARATED OCCUPANCIES FIRE-RESISTANCE RATING NOW INCREASED	2009	MODIFICATION			
509	CONCEPT OF INCIDENTAL USES CLARIFIED	2012	CLARIFICATION			
509	INCIDENTAL USE ROOMS AND AREAS NOW REQUIRE AUTOMATIC SPRINKLERS	2012	MODIFICATION			
TABLE 509	LIST OF INCIDENTAL USES IS EXPANDED	2012	MODIFICATION			
509.2	HORIZONTAL SEPARATION OF BUILDINGS	2009	MODIFICATION			
509.5 509.6	ALLOWABLE HEIGHT FOR GROUP R- 1 INCREASED	2009	MODIFICATION			
509.9	MULTIPLE BUILDINGS ABOVE PARKING GARAGES REGULATED AS INDIVIDUAL BUILDINGS	2009	CLARIFICATION			
602, NOTE h	NONBEARING EXTERIOR WALLS OF UNLIMITED OPENINGS NO LONGER	2012	MODIFICATION			

	REQUIRE FIRE RESISTANCE RATING					
602.1	SCOPE OF CHAPTER 6 CLARIFIED IN REGARDS TO FIRE-RESISTANCE OF BUILDING ELEMENTS & PRESENCE OF OPENINGS, JOINTS, DUCTS, ETC.	2009	CLARIFICATION			
603.1	FIRE-RETARDANT-TREATED WOOD WITHIN ROOFS NOW PERMITTED IN TYPE IB CONSTRUCTION	2009	MODIFICATION			
701.2	FOR MULTI-USE FIRE ASSEMBLIES, REQUIREMENTS FOR BOTH TYPES MUST BE MET	2012	CLARIFICATION			
703.4	ESTABLISHING FIRE RESISTANCE RATINGS	2012	CLARIFICATION			
703.6	ABOVE CEILING IDENTIFICATION OF FIRE & SMOKE SEPARATION WALLS NOW REQUIRED	2009	ADDITION			
703.7	IDENTIFICATION FOR SIZE AND LOCATION OF MARKINGS FOR FIRE AND SMOKE SEPARATION WALLS INCREASED	2012	MODIFICATION			
704, 202	FIRE-RESISTANCE RATINGS FOR STRUCTURAL COLUMNS REQUIRE PROTECTION BY INDIVIDUAL ENCASEMENT REGARDLESS OF LOADING CONDITIONS	2009	MODIFICATION			
704.9	CONCRETE COLUMNS IN PARKING GARAGES NO LONGER REQUIRE IMPACT PROTECTION	2009	MODIFICATION			
704.11	SPAN OF LINTEL, SHELF ANGLE BOTTOM FLANGES INCREASED	2012	MODIFICATION			
704.13	SPRAYED FIRE-RESISTANCE MATERIALS NOW SPECIFICALLY REGULATED TO PREVENT DISLODGING	2009	ADDITION			
705.2	REVISED METHOD FOR DETERMINING MAXIMUM PROJECTION BEYOND EXTERIOR WALLS	2009	MODIFICATION			
705.2	SIMPLIFIED THE METHOD FOR DETERMINING MAXIMUM PROJECTIONS BEYOND EXTERIOR	2012	MODIFICATION			

	WALLS					
705.2.3	CREATED MORE RESTRICTIVE PROTECTION OF COMBUSTIBLE PROJECTIONS	2012	MODIFICATION			
705.3	IMAGINARY LINE NOW DETERMINES FIRE PROTECTION REQUIREMENTS FOR BUILDINGS ON THE SAME LOT	2012	MODIFICATION			
705.5	EXTERIOR WALLS REQUIRED TO BE FIRE-RESISTANCE RATED MUST BE RATED FROM BOTH SIDES WHEN DISTANCE IS 10 FEET OR LESS	2009	MODIFICATION			
TABLE 705.8	MAXIMUM PERMITTED AREA OF EXTERIOR WALL OPENINGS IS SLIGHTLY MODIFIED	2009	MODIFICATION			
706.2	DOUBLE FIRE WALL NOW PERMITTED AS AN ALTERNATIVE TO A SINGLE FIRE WALL	2012	ADDITION			
706.5.1	ALTERNATIVE METHOD OF USING AN IMAGINARY LINE REGULATING EXTERIOR WALL AND OPENING PROJECTIONS OF FIRE WALL INTERSECTIONS AT EXTERIOR WALLS	2009	ADDITION			
706.6, 706.6.2	ADDRESSES FIRE WALL HEIGHT AT SLOPED ROOFS	2012	ADDITION			
707.3.9	SEPARATION OF FIRE AREAS SHALL BE THE MINIMUM RATING BASED ON THE MOST RESTRICTIVE OCCUPANCY	2009	CLARIFICATION			
707.8, 707.9	INTERSECTIONS OF FIRE BARRIERS AT ROOF ASSEMBLIES CAN NOW BE PROTECTED BY APPROVED MATERIAL RATHER THAN FIRE-RESISTANT JOINT SYSTEMS	2012	MODIFICATION			
708.2, Exc. 7,14 & 15	AMOUNT OF CONCEALED SPACE ALLOWANCE FOR 2 STORIES OPEN TO EACH OTHER WITHOUT SHAFT PROTECTION	2009	CLARIFICATION			
708.14.1	ELEVATOR LOBBY PROTECTION	2009	MODIFICATION			

	INCREASED FOR GROUP 1-2 OCCUPANCIES					
709.4	CONTINUITY OF SMOKE BARRIERS FOR ELEVATOR LOBBIES & AREAS OF REFUGE	2012	CLARIFICATION			
712	CHAPTER 7 FORMATTING NOW EMPHASIZES PROTECTIVE MEASURES FOR VERTICAL OPENINGS RATHER THAN SHAFT ENCLOSURES AS THE SOLE MEANS OF PROTECTION	2012	CLARIFICATION			
712.9, 407.4.3	HORIZONTAL ASSEMBLIES USED AS SMOKE BARRIERS NOW MORE SPECIFICALLY REGULATED WHERE CONTAINING OPENINGS FOR ELEVATOR SHAFTS, PENETRATIONS & JOINTS	2009	ADDITION			
713.13	REFUSE & LAUNDRY CHUTES IN GROUP I-2 OCCUPANCIES NOW REGULATED BY CHAPTER 5 OF NFPA 82, STANDARD ON INCINERATORS & WASTE & LINEN HANDLING SYSTEMS & EQUIPMENT	2012	MODIFICATION			
713.13.4	FIRE PROTECTION INCREASED FOR REFUSE OR LAUNDRY CHUTE TERMINATION ROOMS	2012	MODIFICATION			
713.14.1	UNDER CERTAIN CRITERIA, ELEVATOR HOISTWAYS IN HIGH-RISE BUILDINGS NO LONGER REQUIRE ELEVATOR LOBBY PROTECTION	2012	MODIFICATION			
714.4.1	APPROVED MATERIAL MUST NOW BE INSTALLED IN OPEN SPACES AT INTERSECTIONS OF EXTERIOR CURTAIN WALLS & NONFIRE-RESISTANCE-RATED FLOOR OR FLOOR ASSEMBLIES.	2009	ADDITION			
714.4.1.1.2	ELIMINATION OF 'T' RATING PROTECTION REQUIREMENT FOR FLOOR PENETRATIONS OF HORIZONTAL ASSEMBLIES	2012	MODIFICATION			

714.4.1.2	CERTAIN CEILING MEMBRANES NOW PERMITTED TO BE INTERRUPTED BY A DOUBLE WOOD TOP PLATE OF A FIRE-RESISTANCE-RATED WALL	2012	MODIFICATION			
714.5, 715.6, 202	'L' RATING IDENTIFYING THE AIR LEAKAGE RATE IS NOW MANDATED FOR PENETRATION FIRESTOP SYSTEMS & FIRE-RESISTANT JOINT SYSTEMS UTILIZED IN SMOKE BARRIER CONSTRUCTION	2012	CLARIFICATION			
715.4	NEW ACCEPTABLE TEST CRITERIA FOR EXTERIOR CURTAIN WALL/FLOOR INTERSECTIONS	2012	MODIFICATION			
716.3, 202	NEW TABLE 716.3 ADDED TO SPECIFY TEST STANDARDS FOR FIRE-RATED GLAZING AS WELL AS DESIGNATED 'MARKINGS' FOR SUCH GLAZING	2012	CLARIFICATION			
716.5	TABLE 715.4 EXPANDED TO INCLUDE SIZE AND MARKING REQUIREMENTS FOR DOOR VISION PANELS, ASSEMBLY RATING & GLAZING MARKING REQUIREMENTS FOR SIDELIGHTS & TRANSOMS.	2012	CLARIFICATION			
716.5.6	FIRE DAMPERS NOW REQUIRED FOR DUCT PENETRATIONS & AIR TRANSFER OPENINGS OCCURRING IN FIRE-RESISTANCE-RATED EXTERIOR WALLS REQUIRED TO HAVE PROTECTED OPENINGS.	2009	ADDITION			
716.5.5.1	ALLOWANCE FOR GLAZING IN EXIT ENCLOSURE AND EXIT PASSAGEWAY DOORS HAS BEEN REVISED	2012	MODIFICATION			
TABLE 716.6	TABLE 716.6 NOW IDENTIFIES MARKINGS REQUIRED ON FIRE-RATED GLAZING IN SPECIFIED APPLICATIONS	2012	CLARIFICATION			
716.6.4	THE ALLOWANCE FOR USE OF WIRED GLASS WITHOUT COMPLIANCE WITH TEST STANDARDS HAS BEEN DELETED	2012	DELETION			

717.5.4	THE OMISSION OF FIRE DAMPERS IN FIRE PARTITIONS IS NOW PERMITTED UNDER THE SAME CRITERIA PREVIOUSLY ESTABLISHED FOR FIRE BARRIERS	2012	MODIFICATION			
718.2.6	FIREBLOCKING WITHIN EXTERIOR WALL COVERINGS NO LONGER REQUIRED WHERE WALL COVERING IS TESTED AND INSTALLED IN CONFORMANCE WITH NFPA 285	2012	MODIFICATION			
801.2	CHAPTER 8 HAS BEEN REFORMATTED IN ITS ENTIRETY TO ALLOW FOR A MORE APPROPRIATE METHODOLOGY IN THE APPLICATION OF PROVISIONS ADDRESSING INTERIOR FLOOR & WALL FINISHES	2009	CLARIFICATION			
803.11.4	MAX. ¼" THICK CLASS A MATERIALS NO LONGER PERMITTED AS INTERIOR WALL OR CEILING FINISHES WHERE SUSPENDED OR SET OUT FROM THEIR BACKING UNLESS NONCOMBUSTIBLE	2009	MODIFICATION			
803.12	POLYPROPYLENE PLASTICS USED AS INTERIOR FINISHES MUST NOW MEET NEW TESTING CRITERIA	2012	MODIFICATION			
803.13	NEW TESTING STANDARDS FOR SITE-FABRICATED STRETCH SYSTEMS	2009	ADDITION			
804.4	INTERIOR FLOOR FINISH REQUIREMENTS FOR FIBROUS FLOORING	2012	CLARIFICATION			
804.4.1	GROUP I-1 FLOOR COVERING CLASSIFICATION IN EXITWAYS IS NOW CLASS 1 (NONSPRINKLERED) & CLASS II (SPRINKLERED)	2009	ADDITION			
901.8	PUMP & RISER ROOM SIZED TO FACILITATE MAINTENANCE	2012	ADDITION			
902.1	THE DEFINITION OF FIRE AREA NOW INCLUDES UNENCLOSED FLOOR AREA WITH A ROOF OR FLOOR ABOVE	2009	MODIFICATION			

903.2.2	SPRINKLERS IN GROUP B AMBULATORY CARE FACILITIES NOW REGULATED ON A FLOOR-BY-FLOOR BASIS	2012	MODIFICATION			
903.2.3	FIRE SPRINKLERS IN GROUP E OCCUPANCY NOW REQUIRED AT 12,000 SQ. FT. NOT 20,000 SQ. FT.	2009	MODIFICATION			
903.2.7	SPRINKLERS REQUIRED IN GROUP M OCCUPANCIES THAT SELL OR DISPLAY UPHOLSTERED FURNITURE	2009	MODIFICATION			
903.2.4, 903.2.7, 903.2.9	SPRINKLERS NOW REQUIRED IN ALL OCCUPANCIES WHERE UPHOLSTERED FURNITURE OR MATTRESSES ARE MANUFACTURED, STORED OR DISPLAYED	2012	MODIFICATION			
903.2.10	ENCLOSED PARKING GARAGES NOT BENEATH OCCUPANCY GROUPS NOW ONLY REQUIRE SPRINKLERS WHEN THE FIRE AREA CONTAINING THE PARKING GARAGE EXCEEDS 12,000 SQ. FT.	2009	MODIFICATION			
903.2.11.1	THE METHOD FOR THE DISTRIBUTION OF EXTERIOR WALL OPENINGS FOR FIRE DEPARTMENT ACCESS TO NON-SPRINKLERED STORIES & BASEMENTS IS CLARIFIED	2009	CLARIFICATION			
903.2.11.1.3	BASEMENTS WITH WALLS, PARTITIONS OR FIXTURES THAT OBSTRUCT WATER FROM HOSE STREAMS NOW REQUIRE AUTOMATIC SPRINKLERS	2012	MODIFICATION			
903.2.11.2	SPRINKLER PROTECTION OF RUBBISH & LINEN CHUTES	2012	MODIFICATION			
903.3.1.2.1	SPRINKLER PROTECTION OF DWELLING UNIT EXTERIOR DECKS & BALCONIES IS NOW REQUIRED ONLY WHEN THERE IS A COMBUSTIBLE DECK OR ROOF ABOVE	2009	MODIFICATION			

903.3.1.3	THE REFERENCES TO NFPA 13D SPRINKLER SYSTEMS INSTALLED IN ONE AND TWO FAMILY DWELLINGS HAS BEEN EXTENDED TO INCLUDE TOWNHOUSES	2009	ADDITION			
903.3.5.2	SECONDARY WATER SUPPLIES MUST NOW BE DESIGNED TO OPERATE AUTOMATICALLY	2012	MODIFICATION			
904.3.2	NOW ALL MULTIPLE FIRE-EXTINGUISHING SYSTEMS MUST BE DESIGNED TO OPERATE SIMULTANEOUSLY	2012	MODIFICATION			
905.4	REQUIREMENTS FOR ROOF HOSE CONNECTIONS ON CLASS 1 STANDPIPES HAVE BEEN CLARIFIED	2012	MODIFICATION			
906	IFC PROVISIONS FOR PORTABLE FIRE EXTINGUISHERS HAVE BEEN ADDED TO THE IBC	2009	ADDITION			
906.1	PORTABLE FIRE EXTINGUISHERS IN GROUP R-2 OCCUPANCIES NO LONGER REQUIRED IF ONE IS PROVIDED IN EACH INDIVIDUAL UNIT	2012	MODIFICATION			
907.2, EXCEPTIONS	CLARIFIED REQUIREMENTS FOR SINGLE MANUAL FIRE ALARM BOXES IN SPRINKLERED R-2 OCCUPANCIES	2009	MODIFICATION			
907.2.1	FIRE ALARM SYSTEMS REQUIREMENTS IN BUILDINGS WITH TWO OR MORE GROUP A OCCUPANCIES NOW BASED ON WHETHER THEY ARE IN SEPARATE FIRE AREAS	2012	MODIFICATION			
907.2.1.2	MASS NOTIFICATION FIRE ALARM SYSTEMS IN LARGE STADIUMS, ARENAS AND GRANDSTANDS NOW REQUIRE CAPTIONED MESSAGES	2012	ADDITION			
907.2.3	EMERGENCY VOICE/ALARM COMMUNICATIONS SYSTEM NOW REQUIRED IN GROUP E OCCUPANCIES WITH AN OCCUPANT LOAD OF 30 OR MORE	2012	MODIFICATIONS			

907.2.9.3	SMOKE DETECTION SYSTEMS IN GROUP R-2 COLLEGE BUILDINGS ARE NOW REQUIRED	2012	ADDITION			
907.2.11.3	SMOKE ALARM INTERCONNECTION REQUIREMENTS NOW APPLY TO GROUP I-1 OCCUPANCIES AND ALLOW FOR USE OF WIRELESS ALARMS	2012	MODIFICATION			
908.7	IN NEW & EXISTING BUILDINGS OF GROUP R AND I OCCUPANCIES WITH FUEL-BURNING APPLIANCES OR ATTACHED GARAGES, CARBON MONOXIDE ALARMS ARE NOW REQUIRED	2012	ADDITION			
913, 913.2.1	ROOMS INSIDE BUILDINGS THAT HOUSE FIRE PUMPS NOW REQUIRE FIRE-RESISTANT SEPARATION IN ACCORDANCE WITH THE IBC	2009	ADDITION			
914	REQUIREMENTS IN THE IFC FOR IDENTIFICATION OF SHAFTWAY HAZARDS & THE LOCATION OF FIRE PROTECTION SYSTEMS ARE NOW INCLUDED IN THE IBC	2009	ADDITION			
1001.4	FIRE SAFETY & EVACUATION PLANS NOW REFERENCE THE IFC PROVISIONS FOR CONSISTENCY	2012	ADDITION			
1002.1	THE DEFINITIONS OF SEVERAL MEANS OF EGRESS TERMS HAVE BEEN ADDED OR REVISED	2009	ADDITION			
1004.1.2, TABLE 1004.1.2	AN OCCUPANT LOAD FACTOR FOR MUSEUMS & EXHIBIT GALLERIES HAS BEEN ESTABLISHED AS 30 SQUARE FEET PER OCCUPANT	2012	MODIFICATION			
1005	REDUCED EXIT WIDTH FACTORS HAVE BEEN ESTABLISHED FOR BUILDINGS THAT MEET CERTAIN CRITERIA	2012	MODIFICATION			
1005.2, 1005.3	THE METHOD OF MEASUREMENT FOR MEANS OF EGRESS WIDTH HAS BEEN SPECIFICALLY ADDRESSED	2009	MODIFICATION			

1007	EXTERIOR AREAS FOR ASSISTED RESCUE CAN NOW BE PROVIDED ON STORIES ABOVE THE LEVEL OF EXIT DISCHARGE. IN ADDITION, OPEN INTERIOR EXIT ACCESS STAIRWAYS ARE NOW RECOGNIZED AS ACCESSIBLE MEANS OF EGRESS COMPONENTS	2012	MODIFICATION			
1007.3, 1007.4	AREAS OF REFUGE ARE NO LONGER MANDATED AS REQUIRED ELEMENTS OF ACCESSIBLE MEANS OF EGRESS IN THOSE BUILDINGS EQUIPPED THROUGHOUT WITH AN AUTOMATIC SPRINKLER SYSTEM	2009	MODIFICATION			
1007.6.3, 1007.8	A MEANS OF TWO-WAY COMMUNICATION IS NOW ALSO REQUIRED IN MULTI-STORY BUILDINGS IN WHICH AREAS OF REFUGE ARE NOT PROVIDED	2009	ADDITION			
1008.1.2, EXCEPTION 9	A MANUALLY OPERATED HORIZONTAL SLIDING DOOR IS NOW PERMITTED AS A MEANS OF EGRESS ELEMENT IN OCCUPANCIES OTHER THAN GROUP H, PROVIDED THE OCCUPANT LOAD IS LIMITED	2009	ADDITION			
1008.1.2	THE OCCUPANT LOAD USED TO DETERMINE THE DOOR SWING REQUIREMENTS IS NOT TO BE BASED ON AN ASSIGNED OR DISTRIBUTED OCCUPANY LOAD, BUT ON THE ENTIRE OCCUPANT LOAD OF THE SPACE SERVED BY THE DOOR	2012	CLARIFICATION			
1008.1.9.4	THE ALLOWANCE FOR THE USE OF MANUALLY OPERATED EDGE OR SURFACE MOUNTED BOLTS ON THE INACTIVE LEAF OF A PAIR OF DOORS HAS BEEN EXTENDED TO LIMITED APPLICATIONS IN GROUP B, F, S, AND I-2 OCCUPANCIES	2009	ADDITION			

1008.1.9.6	THE INSTALLATION OF LOCKING DEVICES NOT USABLE BY THE PATIENTS OF A GROUP I-2 OCCUPANCY IS NOW PERMITTED WHERE MULTIPLE CONDITIONS ARE MET	2009	ADDITION			
1008.1.9.8	ELECTROMAGNETICALLY LOCKING EGRESS DOORS ARE NOW PERMITTED IN LIMITED OCCUPANCIES UNDER CERTAIN CONDITIONS	2009	ADDITION			
1008.1.9.9	USE OF ELECTROMAGNETICALLY LOCKING DOORS IS EXPANDED	2012	MODIFICATION			
1008.1.10.1	PANIC HARDWARE AND FIRE EXIT HARDWARE INSTALLED ON MEANS OF EGRESS DOORS MUST NOW BE LISTED IN ACCORDANCE WITH UL 305, PANIC HARDWARE	2009	CLARIFICATION			
1009, 1010, 202	REVISIONS HAVE BEEN MADE FOR INTERIOR STAIRWAYS & RAMPS TO BE USED AS A PORTION OF THE MEANS OF EGRESS	2012	CLARIFICATION			
1009.1	STAIRWAY PROVISIONS ARE NOW EXPANDED TO INCLUDE EVEN 'CONVENIENCE' STAIRWAYS THAT ARE NOT A PORTION OF A REQUIRED MEANS OF EGRESS	2012	CLARIFICATION			
1009.4.5, EXCEPTION 2	OPEN RISERS IN GROUP F, H, AND S OCCUPANCIES ARE NOW PERMITTED AT STAIRWAYS LOCATED IN AREAS NOT ACCESSIBLE TO THE PUBLIC	2009	MODIFICATION			
1009.9	THE METHOD OF DETERMINING THE WIDTH OF A SPIRAL STAIRWAY HAS BEEN MODIFIED	2009	MODIFICATION			
1009.12	IN DWELLING AND SLEEPING UNITS OF GROUP R-2 & R-3 OCCUPANCIES, A HANDRAIL IS NOW REQUIRED ONLY FOR STAIRS HAVING FOUR OR MORE RISERS	2009	MODIFICATIONS			

1009.14	WHERE ACCESS TO A ROOF OR PENTHOUSE IS REQUIRED TO MAINTAIN ELEVATOR EQUIPMENT, A STAIRWAY MUST NOW BE PROVIDED FOR ACCESS PURPOSES	2009	ADDITION			
1010.9.1	THE MINIMUM REQUIRED HEIGHT OF 4 INCHES FOR A CURB USED AS EDGE PROTECTION AT THE SIDE OF RAMPS AND RAMP LANDINGS HAS BEEN CLARIFIED	2009	CLARIFICATION			
1011.1	EXIT SIGNS ARE NOW REQUIRED WITHIN EXITS AND INTERVENING DOORS WITHIN EXITS TO CLEARLY INDICATE THE DIRECTION OF MEANS OF EGRESS TRAVEL	2009	MODIFICATION			
1011.2	WHERE GENERAL-USE EXIT SIGNS ARE REQUIRED IN GROUP R-1 OCCUPANCIES, LOW-LEVEL EXIT SIGNS MUST ALSO BE PROVIDED IN THE MEANS OF EGRESS SERVING THE GUEST ROOMS	2012	ADDITION			
1011.4	INTERNALLY ILLUMINATED EXIT SIGNS ARE NOW REQUIRED TO BE LISTED AND LABELED PER UL 924	2009	MODIFICATION			
1012.2	THE HANDRAIL HEIGHT FOR ALTERNATING TREAD DEVICES HAS BEEN MODIFIED	2009	MODIFICATION			
1012.2	TRANSITION PIECES OF A CONTINUOUS HANDRAIL ARE NOW PERMITTED TO EXCEED THE MAXIMUM PERMITTED HANDRAIL HEIGHT	2012	MODIFICATION			
1012.3	CRITERIA HAS BEEN PROVIDED FOR ADDITIONAL COMPLYING HANDRAIL SHAPES	2009	ADDITION			
1012.3.1, 1012.8	A MINIMUM CROSS-SECTION DIMENSION HAS NOW BEEN ESTABLISHED FOR THE GRASPABILITY OF NONCIRCULAR TYPE I HANDRAILS	2012	MODIFICATION			

1013.1	THE METHOD FOR DETERMINING WHERE A GUARD IS REQUIRED HAS BEEN MODIFIED	2009	MODIFICATION			
1013.1, 1013.8	THE GUARD REQUIREMENTS FOR OPERABLE WINDOWS HAS BEEN REVISED	2012	MODIFICATION			
1013.2	FIXED SEATING ADJACENT TO A GUARD IS NOW CONSIDERED A WALKING SURFACE AND THE MINIMUM HEIGHT OF THE GUARD IS TO BE MEASURED FROM THAT SURFACE RATHER THAN FROM THE FLOOR	2009	MODIFICATION			
1013.3	THE PERMITTED MAXIMUM SIZE OF OPENINGS IN THE UPPER PORTION OF GUARDS HAS BEEN REDUCED FROM 8 INCHES TO 4 3/8 INCHES	2009	MODIFICATION			
1013.3	THE MINIMUM HEIGHT FOR GUARDS IN GROUP R-3 OCCUPANCIES AND WITHIN INDIVIDUAL GROUP R-2 DWELLING UNITS HAS BEEN DECREASED FROM 42 INCHES TO 36 INCHES	2012	MODIFICATION			
1014.3	AN ALLOWANCE FOR AN EXTENDED COMMON PATH OF EGRESS TRAVEL IN GROUP R-2 OCCUPANCIES IS NOW ALSO AVAILABLE IN BUILDINGS THAT ARE PROTECTED THROUGHOUT WITH AN NFPA 13R AUTOMATIC SPRINKLER SYSTEM	2009	MODIFICATION			
1015.1	THE OCCUPANT LOAD THRESHOLD AT WHICH A SECOND MEANS OF EGRESS IS REQUIRED FROM A GROUP R-2 OCCUPANCY HAS BEEN INCREASED FROM 11 TO 21 IN BUILDINGS WITH AN AUTOMATIC SPRINKLER SYSTEM	2009	MODIFICATION			

1016.1	THE APPROPRIATE MEASUREMENT OF TRAVEL DISTANCE HAS BEEN CLARIFIED TO INDICATE THAT IT INCLUDES TRAVEL ON UNENCLOSED EXIT ACCESS STAIRWAYS	2009	CLARIFICATION			
1016.2	THE ALLOWANCE FOR AN INCREASED TRAVEL DISTANCE IN SPRINKLERED GROUP F-1 & S-1 OCCUPANCIES THAT ARE PROVIDED WITH AUTOMATIC SMOKE AND HEAT VENTS HAS BEEN ELIMINATED	2009	DELETION			
1018.4	THE PERMISSIBLE LENGTH OF A DEAD-END CORRIDOR HAS BEEN EXTENDED TO 50 FEET IN GROUP E, I-1, M, R-1, R-2, R-4, S, AND U OCCUPANCIES IF THE BUILDING IS PROVIDED THROUGHOUT WITH AN NFPA 13 AUTOMATIC SPRINKLER SYSTEM	2009	MODIFICATION			
1021.2, TABLE 1021.2	THE ALLOWANCE FOR SINGLE-EXIT BUILDINGS HAS BEEN CLARIFIED TO ADDRESS EGRESS FROM INDIVIDUAL STORIES WITHIN THE BUILDINGS	2009	CLARIFICATION			
1021.2	EXITS ARE NOW PERMITTED TO BE ARRANGED WHERE THEY SERVE A PORTION OF A STORY INSTEAD OF REQUIRING THAT ALL OF THE REQUIRED EXITS FROM THE STORY BE ACCESSIBLE TO ALL OF THE OCCUPANTS	2012	MODIFICATION			
1021.2.1	A RATIO EQUATION IS NOW TO BE USED TO DETERMINE IF A SINGLE EXIT IS ALLOWED TO SERVE THE COMBINED OCCUPANT LOAD FROM DIFFERENT OCCUPANCIES	2012	CLARIFICATION			
1021.2.3, TABLE 1021.2(1)	A NEW SECTION CLARIFIES WHEN A SINGLE EXIT IS PERMITTED WITHIN OR FROM AN INDIVIDUAL DWELLING UNIT.	2012	MODIFICATION			

1022.1	THE FIRE-RESISTANCE RATING OF AN EXIT ENCLOSURE CANNOT BE LESS THAN THE RATING OF THE FLOOR CONSTRUCTION PENETRATED BY THE ENCLOSURE	2009	CLARIFICATION			
1022.5	PENETRATIONS OF THE OUTSIDE MEMBRANE OF A FIRE BARRIER UTILIZED TO ENCLOSE AN INTERIOR EXIT STAIR OR RAMP ARE NOW PERMITTED PROVIDED THE PENETRATION IS PROPERLY PROTECTED	2012	MODIFICATION			
1024	PHOTOLUMINESCENT OR SELF-LUMINOUS EXIT PATH MARKINGS ARE NOW REQUIRED IN EXIT ENCLOSURES AND EXIT PASSAGEWAYS OF SPECIFIED HIGH-RISE BUILDINGS IN ORDER TO DELINEATE THE EXIT PATH	2009	ADDITION			
1028.1	ASSEMBLY USES CLASSIFIED AS GROUP E OCCUPANCIES ARE NOW SUBJECT TO THE SPECIFIC MEANS OF EGRESS PROVISIONS SET FORTH FOR GROUP A OCCUPANCIES IN SECTION 1028	2009	MODIFICATION			
1028.1.1.1	SPACES BENEATH GRANDSTANDS AND BLEACHERS ARE NOW REQUIRED TO BE ADEQUATELY SEPARATED TO PROTECT THE ASSEMBLY SEATING AREA FROM ANY POTENTIAL HAZARDS	2012	ADDITION			
1028.4	THE PHYSICAL BARRIER REQUIRED TO SEPARATE THE WAITING AREAS WITHIN LOBBIES OF GROUP A-1 OCCUPANCIES FROM THE MEANS OF EGRESS PATHS IS NO LONGER MANDATED	2009	MODIFICATION			

1103.2.3	THE MAXIMUM SIZE OF THOSE EMPLOYEE WORK AREAS SPECIFICALLY EXEMPTED FROM ALL ACCESSIBILITY REQUIREMENTS HAS BEEN INCREASED FROM 150 SQUARE FEET TO 300 SQUARE FEET	2009	MODIFICATION			
1103.2.13	THE DEGREE OF ACCESSIBILITY REQUIRED IN A LIVE/WORK UNIT HAS BEEN ESTABLISHED BASED ON A DISTINCTION BETWEEN THE RESIDENTIAL USE AND THE BUSINESS OR MERCHANTILE ACTIVITY	2009	ADDITION			
1104.3.1	WHERE AN EMPLOYEE WORK AREA IS LESS THAN 1000 SQUARE FEET IN FLOOR AREA, THE COMMON USE CIRCULATION PATH NEED NOT MEET ACCESSIBLE ROUTE REQUIREMENTS	2012	MODIFICATION			
1006.5	WHERE A REQUIRED ACCESSIBLE VAN SPACE IS LOCATED WITHIN A PRIVATE GARAGE SERVING A GROUP R-2 OR R-3 OCCUPANCY, THE MINIMUM VERTICAL CLEARANCE NEED BE ONLY 7 FEET ABOVE THE GARAGE FLOOR	2009	MODIFICATION			
1107.3	THE MANEUVERING CLEARANCE MANDATED ADJACENT TO PASSAGE DOORS IS NO LONGER REQUIRED AT THE ROOM SIDE OF DOORS TO SLEEPING UNITS IN GROUP I-1 FACILITIES	2009	MODIFICATION			
1107.6.1	A REDUCED NUMBER OR PERCENTAGE OF THE FACILITIES IN ACCESSIBLE UNITS ARE NOW REQUIRED TO BE ACCESSIBLE	2012	MODIFICATION			
TABLE 1107.6.1.1	THE REQUIRED TYPE OF BATHING FACILITIES IN ACCESSIBLE DWELLING & SLEEPING UNITS HAS BEEN MODIFIED TO OFFER THE SAME BATHING OPTIONS FOUND IN STANDARD ROOMS	2009	MODIFICATION			

1108.2.7.3	THE CAPTIONING OF AUDIBLE PUBLIC ANNOUNCEMENTS IS NOW ONLY REQUIRED FOR ASSEMBLY SPACES HAVING A PUBLIC ADDRESS SYSTEM AND 15,000 OR MORE SEATS	2012	MODIFICATION			
1108.4.1	THE GENERAL REQUIREMENT FOR COURTROOM ACCESSIBILITY HAS BEEN REPLACED WITH SEVERAL PROVISIONS THAT ADDRESS ELEMENTS SPECIFIC TO THE JUDICIAL ACTIVITIES THAT OCCUR	2009	MODIFICATION			
1109.2, 1109.5	TOILET FACILITIES AND DRINKING FOUNTAINS THAT ARE 'PRIMARILY FOR CHILDREN'S USE' MAY NOW BE INSTALLED AT A LOWER HEIGHT THAT GENERALLY PERMITTED FOR ACCESSIBLE ELEMENTS AND CONSIDERED AS THE REQUIRED ELEMENTS	2012	MODIFICATION			
1109.2.3	A LAVATORY WITH ENHANCED REACH RANGES IS NOW REQUIRED IN A TOILET ROOM OR BATHING FACILITY THAT IS PROVIDED WITH SIX OR MORE LAVATORIES	2009	ADDITION			
1109.6	SAUNAS AND STEAM ROOMS ARE NOW SPECIFICALLY IDENTIFIED AS FEATURES AND FACILITIES THAT MUST BE ACCESSIBLE	2012	ADDITION			
1109.12.1	IN GROUP R-2 APARTMENT HOUSES, MONASTARIES, AND CONVENTS IN WHICH ACCESSIBLE ROOMS IN TYPE A UNITS ARE PROVIDED WITH OPERABLE WINDOWS, AT LEAST ONE WINDOW IN EACH ROOM SHALL BE ACCESSIBLE	2009	CLARIFICATION			

1110.4	VARIABLE MESSAGE SIGNS IN TRANSPORTATION FACILITIES AND EMERGENCY SHELTERS ARE NOW REQUIRED TO COMPLY WITH THE PROVISIONS OF THE A117.1-2009 STANDARD	2012	ADDITION			
1203.1	THE OPTION OF NATURAL VENTILATION RATHER THAN MECHANICAL VENTILATION IS NOW UNAVAILABLE WHEN A DWELLING UNIT IS TESTED USING A BLOWER DOOR TEST AND IT IS DETERMINED THAT AN ADEQUATE NUMBER OF AIR CHANGES ARE NOT PROVIDED	2012	ADDITION			
1203.2	THE MINIMUM REQUIRED VENTILATION AREA FOR ATTICS HAS BEEN CLARIFIED AND EXCEPTIONS ARE NOW PROVIDED THAT EITHER ALLOW A REDUCTION IN THE VENT AREA OR ELIMINATE THE REQUIREMENT COMPLETELY	2012	MODIFICATION			
1208.3	THE MINIMUM FLOOR AREA REQUIREMENT OF 50 SQUARE FEET FOR KITCHENS HAS BEEN DELETED	2012	DELETION			
1210	THE WATER CLOSET COMPARTMENT AND URINAL PARTITION REQUIREMENTS HAVE BEEN RELOCATED FROM CHAPTER 29 TO SECTION 1210	2012	CLARIFICATION			
1210.1	SMOOTH WALL BASE MATERIAL IN TOILET, BATHING AND SHOWER ROOMS IS NOW ALLOWED TO EXTEND UP THE WALL ONLY 4 INCHES	2009	MODIFICATION			
1402.1, 1408	PROVISIONS REGULATING EXTERIOR INSULATION AND FINISH SYSTEMS (EFIS) HAVE BEEN EXPANDED TO INCLUDE REFERENCES TO OTHER SECTIONS OF THE IBC AND NEW ASTM STANDARDS SPECIFIC TO EFIS	2009	ADDITION			

1507.16	THE IBC NOW PROVIDES A REFERENCE TO NEW IFC PROVISIONS ON ROOF GARDENS AND LANDSCAPED ROOFS AS A MEANS OF CONTROLLING THE POTENTIAL HAZARDS THESE COMBUSTIBLE MATERIALS ON THE ROOF COULD CREATE	2012	ADDITION			
1507.17, 3111, 202	PHOTOVOLTAIC ELEMENTS MUST NOW MEET THE GENERAL CODE REQUIREMENTS FOR ROOFING MATERIALS & ROOFTOP STRUCTURES	2012	ADDITION			
1509, 202	TECHNICAL CHANGES & PROVISIONS ADDRESSING ROOFTOP STRUCTURES HAVE BEEN REFORMATTED	2012	MODIFICATION			
1509.2	THE HEIGHT, AREA, AND USE LIMITATIONS FOR PENTHOUSES AND SIMILAR ROOFTOP STRUCTURES NOW ARE NOT TO BE INCLUDED IN THE BUILDING AREA OR FIRE AREA	2009	CLARIFICATION			
1509.2.4	THE USE OF FIRE-RETARDANT-TREATED WOOD IS NOW PERMITTED FOR PENTHOUSES	2009	MODIFICATION			
1510.3	EXISTING ICE DAMS ARE NOW PERMITTED TO REMAIN IN PLACE WHEN REPLACING A ROOF COVERING	2012	MODIFICATION			
CHAPTER 16, CHAPTER 35	SUPPLEMENT #2 TO THE 2005 EDITION OF ASCE/SEI 7 IS NOW REFERENCED IN CHAPTER 16 AND IT REVISES THE MINIMUM BASE SHEAR EQUATIONS FOR BOTH BUILDINGS AND NON BUILDING STRUCTURES	2009	MODIFICATION			
1602, TABLE 1607.1	DECKS & BALCONIES NOW HAVE THE SAME LIVE LOAD AS THE OCCUPANCY THEY SERVE. THE DISTINCTION BETWEEN DECKS AND BALCONIES WAS REMOVED BY DELETING THE DEFINITIONS	2009	MODIFICATION			

1604.3	DEFLECTION LIMITS FOR ROOF & WALL MEMBERS SUPPORTING PLASTER OR STUCCO HAVE BEEN CLARIFIED	2012	MODIFICATION			
1604.5, 202	THE TERM "OCCUPANCY CATEGORY" HAS BEEN CHANGED TO "RISK CATEGORY" TO BETTER REFLECT THE INTENDED MEANING AND TO COORDINATE WITH THE TERMINOLOGY USED IN ASCE 7-10	2012	MODIFICATION			
1604.8.2	ALL WALLS MUST NOW BE ANCHORED TO FLOORS, ROOFS, AND OTHER STRUCTURAL ELEMENTS THAT PROVIDE LATERAL SUPPORT FOR THE WALL	2009	MODIFICATION			
1604.8.3	LOADING CONDITIONS ON CANTILEVERED DECKS HAVE BEEN MODIFIED	2009	MODIFICATION			
1605.1.1	IF FACTORED LOADS ARE USED WHEN PERFORMING STABILITY ANALYSIS OF STRUCTURES, SOIL RESISTANCE AND STRENGTH REDUCTION FACTORS MUST NOW BE CONSIDERED	2009	ADDITION			
1605.2	THE STRENGTH DESIGN LOAD COMBINATIONS IN THE 2012 IBC HAVE BEEN COORDINATED WITH SECTION 2.3 OF ASCE 7-10 AND EXPANDED TO INCLUDE LOADS DUE TO FLUIDS, F, AND OTHER LATERAL PRESSURES, H, AS WELL AS ICE LOADS	2012	MODIFICATION			
1605.3	THE ALLOWABLE STRESS DESIGN LOAD COMBINATIONS IN THE 2012 IBC HAVE BEEN COORDINATED WITH SECTION 2.4 OR ASCE 7-10 & EXPANDED TO INCLUDE LOADS DUE TO FLUIDS, F, AND OTHER LATERAL PRESSURES, H, AS WELL AS ICE LOADS	2012	MODIFICATION			

1605.3.1 & 1605.3.2	THE ALLOWABLE STRESS DESIGN LOAD COMBINATIONS ARE NOW CONSISTENT WHERE ROOF LIVE LOAD AND EARTHQUAKE LOAD EFFECTS ARE COMBINED	2009	MODIFICATION			
TABLE 1607.1	THE LIVE LOADS ESTABLISHED IN IBC SECTION 1607 & TABLE 1607.1 HAVE BEEN MODIFIED AND UPDATED IN ORDER TO COORDINATE WITH THE LIVE LOADS OF CHAPTER 4 & TABLE 4-1 IN ASCE 7-10	2012	MODIFICATION			
1607.6, 202	THE TERMINOLOGY & LIVE LOAD DESIGN REQUIREMENTS FOR HELICOPTER LANDING AREAS (HELIPADS) HAVE BEEN UPDATED & COORDINATED WITH ASCE 7-10	2012	MODIFICATION			
1607.7	PROVISIONS RELATING TO THE DESIGN OF STRUCTURES THAT SUPPORT HEAVY VEHICLE LOADS IN EXCESS OF 10,000 POUNDS GROSS VEHICLE WEIGHT (GVW) HAVE BEEN UPDATED	2012	MODIFICATION			
1607.7.1.3	THE ALLOWANCE FOR A 1/3 STRESS INCREASE FOR THE ALLOWABLE STRESS DESIGN OF HANDRAILS AND GUARDS HAS BEEN DELETED	2009	DELETION			
1607.7.3	ADDS A SECOND APPLICATION OF LOADING FOR PARKING STRUCTURE VEHICLE BARRIERS ADDRESSING HEAVIER AND TALLER VEHICLES	2009	MODIFICATION			
1607.11.2.2	REMOVES THE LIVE LOAD REDUCTION FOR SPECIAL PURPOSE ROOFS OF GROUP A OCCUPANCIES	2009	MODIFICATION			
1608.3, 1611.2, 202	A DEFINITION OF "SUSCEPTIBLE BAY" HAS BEEN ADDED TO IDENTIFY WHERE PONDING MUST BE CONSIDERED IN THE DESIGN OF ROOF STRUCTURES	2012	MODIFICATION			

1613.6.7	REQUIREMENTS FOR MINIMUM BLDG SEPARATION THAT WERE IN PRIOR EDITIONS OF THE IBC HAVE BEEN RESTORED AND A MINIMUM REQUIRED SEPARATION DISTANCE BETWEEN ADJOINING BUILDINGS THAT ARE NOT STRUCTURALLY CONNECTED HAS BEEN ESTABLISHED	2009	ADDITION			
1613.6.8	THE EXCEPTIONS FROM SEISMIC BRACING REQUIREMENTS OF SECTION 13.6.7 OF ASCE 7 HAVE BEEN EXTENDED TO INCLUDE SMALL DUCTS	2009	MODIFICATION			
1613.7	THE REQUIREMENTS FOR ANCHORAGE OF WALLS HAS BEEN REPLACED	2009	ADDITION			
1614	MINIMUM STRUCTURAL INTEGRITY REQUIREMENTS HAVE BEEN PROVIDED FOR HIGH-RISE BUILDINGS ASSIGNED TO OCCUPANCY CATEGORIES III & IV	2009	ADDITION			
1614, 202	A NEW SECTION, DEFINITION AND NOTATION FOR ICE LOADS ON ICE SENSITIVE STRUCTURES HAVE BEEN ADDED TO THE CODE IN ORDER TO PROVIDE CONSISTENCY WITH ASCE 7-10	2012	ADDITION			
1704	THE REQUIREMENTS PERTAINING TO SPECIAL INSPECTOR QUALIFICATIONS HAVE BEEN CLARIFIED, AND THE SPECIAL INSPECTION EXEMPTION FOR GROUP R-3 OCCUPANCIES HAS BEEN DELETED	2009	MODIFICATION			
1704.3	THE PROVISIONS REQUIRING SPECIFIC ITEMS TO HAVE SPECIAL INSPECTION AND THE INFO REQUIRED TO BE INCLUDED HAS BEEN CHANGED	2012	MODIFICATION			

TABLE 1704.4	CONTINUOUS SPECIAL INSPECTION IS NOW REQUIRED FOR CAST-IN-PLACE BOLTS INSTALLED IN CONCRETE WHERE STRENGTH DESIGN IS USED, AND PERIODIC SPECIAL INSPECTION IS NOW MANDATED FOR ANCHORS POST-INSTALLED IN HARDENED CONCRETE	2009	MODIFICATION			
1704.3.4, 1704.6.2	TWO NEW SECTIONS HAVE BEEN ADDED TO REQUIRE THAT THE SPECIAL INSPECTOR VERIFY THAT TEMPORARY AND PERMANENT BRACING ARE INSTALLED IN ACCORDANCE WITH THE APPROVED TRUSS SUBMITTAL PACKAGE FOR BOTH COLD-FORMED STEEL AND WOOD TRUSSES	2009	ADDITION			
1705.2	SPECIAL INSPECTION REQUIREMENTS FOR STRUCTURAL STEEL HAVE BEEN DELETED FROM CHAPTER 17 BECAUSE THE NEW STANDARD FOR STRUCTURAL STEEL BUILDINGS (ANSI/AISC 360-10) INCLUDES QUALITY ASSURANCE PROVISIONS	2012	MODIFICATION			
TABLE 1705.3	THE TYPE OF SPECIAL INSPECTION REQUIRED FOR ANCHORS CAST IN CONCRETE AND POST INSTALLED ANCHORS IN HARDENED CONCRETE HAVE BEEN CLARIFIED	2012	MODIFICATION			
1705.4	REQUIREMENTS FOR SPECIAL INSPECTION OF MASONRY CONSTRUCTION HAVE BEEN DELETED FROM CHAPTER 17 OF THE 2012 IBC BECAUSE OTHER AGENCY REFERENCES SPECIFY THOSE REQUIREMENTS	2012	MODIFICATION			

1803, 1804	THE PROVISIONS RELATED TO GEOTECHNICAL INVESTIGATIONS AND EXCAVATION, GRADING, AND FILL HAVE BEEN REORGANIZED AND CLARIFIED AND THE APPROPRIATE TERM, GEOTECHNICAL, IS NOW CONSISTENTLY USED AS IT RELATES TO GEOTECHNICAL INVESTIGATIONS AND GEOTECHNICAL REPORTS	2009	MODIFICATION			
1803.5.12	THE REQUIREMENT THAT GEOTECHNICAL REPORTS ADDRESS EARTHQUAKE LOADS ON FOUNDATION WALLS AND RETAINING WALLS IN SEISMIC DESIGN CATEGORIES D,E, AND F HAS BEEN MODIFIED SO THAT IT ONLY APPLIES TO THOSE WALLS SUPPORTING MORE THAN 6 FEET OF BACKFILL	2012	MODIFICATION			
1807	MODIFIES THE FACTOR OF SAFETY AGAINST SLIDING FOR RETAINING WALLS	2009	MODIFICATION			
1807.2	IN THE DESIGN ANALYSIS FOR A RETAINING WALL, LATERAL SOIL PRESSURE ON BOTH SIDES OF THE KEYWAY ARE NOW EXPLICITLY REQUIRED TO BE CONSIDERED IN THE SLIDING ANALYSIS	2009	MODIFICATION			
1808.3.1	CONSISTENCY IS NOW PROVIDED BETWEEN THE IBC AND ASCE 7 REGARDING THE REDUCTION OF SEISMIC	2009	MODIFICATION			
1810.3.1.5	PROVISIONS HAVE BEEN ADDED REGULATING THE DESIGN AND INSTALLATION OF HELICAL PILE FOUNDATIONS	2009	MODIFICATION			

1810.3.3.1.6	THE UPLIFT CAPACITY OF PILE GROUPS IS NOW PERMITTED TO INCLUDE TWO-THIRDS OF THE SHEAR RESISTANCE OF THE SOIL BLOCK	2012	MODIFICATION			
CHAPTER 19	THE CONCRETE PROVISIONS OF CHAPTER 19 HAVE BEEN UPDATED AND COORDINATED WITH THE 2008 EDITION OF THE ACI 318 STANDARD	2009	MODIFICATION			
CHAPTER 19	THE PROVISIONS RELATED TO CONCRETE CONSTRUCTION WERE DELETED FROM CHAPTER 19 BECAUSE THEY ARE CONTAINED IN THE 2011 EDITION OF ACI 318	2012	MODIFICATION			
1905.1.3	THIS SECTION AMENDS ACI 318 SECTION 21.4 BY ADDING SEISMIC DETAILING REQUIREMENTS FOR WALL PIERS IN SEISMIC DESIGN CATEGORIES D, E, AND F	2012	ADDITION			
1905.1.8	PLAIN CONCRETE FOOTINGS MAY NOW ONLY SUPPORT DETACHED ONE AND TWO FAMILY DWELLINGS WITH LIGHT FRAME STUD WALLS WHERE SUCH STRUCTURES ARE LOCATED IN SEISMIC DESIGN CATEGORIES A, B, AND C	2012	MODIFICATION			
1905.1.9	PORTIONS OF ACI 318 APPENDIX D HAVE BEEN AMENDED IN RECOGNITION OF THE FACT THAT FAILURE OF THE WOOD SILL PLATE OR THE COLD FORMED STEEL TRACK CONTROL THE CAPACITY OF THE CONNECTION OF THE SHEAR WALL TO THE CONCRETE FOUNDATION	2012	MODIFICATION			
1908.1.16	EXCEPTIONS HAVE BEEN ADDED FOR DUCTILITY FOR CONCRETE WALL ANCHORAGES THAT HAVE BEEN DESIGNED FOR MAXIMUM EXPECTED SEISMIC FORCES	2009	MODIFICATION			

CHAPTER 21	SUBSTANTIAL PORTIONS OF CHAPTER 21 HAVE BEEN DELETED AND SOME PORTIONS HAVE BEEN UPDATED	2009	MODIFICATION			
2101.2	THE NEW TMS 403-10 MASONRY DESIGN STANDARD, NOW REFERENCED IN THE IBC, PROVIDES A DIRECT DESIGN METHOD FOR SIMPLE, SINGLE-STORY, CONCRETE MASONRY BEARING-WALL STRUCTURES	2012	ADDITION			
2111.3, 2113.3	SEISMIC REINFORCING AND ANCHORAGE OF FIREPLACES AND CHIMNEYS NOW ALSO INCLUDES SEISMIC DESIGN CATEGORY C.	2009	MODIFICATION			
2206	PERFORMANCE EVIDENCE REQUIRED FOR COMPOSITE STRUCTURAL STEEL AND CONCRETE STRUCTURES ARE NOW ADDRESSED IN THE 2010 EDITION OF AISC 341 WITH THE ADDITION OF A NEW SECTION	2012	ADDITION			
2208.1	THE LATEST VERSION OF THE RACK MANUFACTURERS INSTITUTE (RMI) STANDARD, WHICH INCLUDES MANY CLARIFICATIONS REGARDING THE SEISMIC DESIGN OF RACKS, IS NOW REFERENCED	2009	MODIFICATION			
2209.1	THE REFERENCE TO AISI'S NORTH AMERICAN SPECIFICATION FOR THE DESIGN OF COLD FORMED STEEL STRUCTURAL MEMBERS, 2007 EDITION, HAS BEEN UPDATED AND GIVEN THE NEW NUMBER DESIGNATION OF AISI S100	2009	MODIFICATION			
2209.2	TWO NEW STEEL DECK INSTITUTE (SDI) STANDARDS FOR THE DESIGN AND CONSTRUCTION OF COLD FORMED STEEL FLOOR AND ROOF DECKS ARE NOW REFERENCED	2009	ADDITION			

2307	THE PROVISIONS IN THIS SECTION DEALING WITH THE LOAD AND RESISTANCE FACTOR DESIGN OF WOOD STRUCTURES ARE NOW COORDINATED WITH THE 2008 EDITION OF THE AF&PA STANDARD, SPECIAL DESIGN PROVISIONS FOR WIND AND SEISMIC (SDPWS-08)	2012	MODIFICATION			
2307.1	A REFERENCE TO THE AF&PA SPECIAL DESIGN PROVISIONS FOR WIND AND SEISMIC (SDPWS) HAS BEEN ADDED TO SECTION 2307 FOR LOAD AND RESISTANCE FACTOR DESIGN (LRFD) OF WOOD STRUCTURES	2309	MODIFICATION			
2308.2	THE LIMITATIONS REGARDING FLOOR-TO-FLOOR AND STUD HEIGHT FOR CONVENTIONAL WOOD FRAME CONSTRUCTION HAVE BEEN CLARIFIED	2009	MODIFICATION			
2308.2	THE PERMITTED USE OF THE CONVENTIONAL LIGHT-FRAME CONSTRUCTION PROVISIONS IN AREAS OF WIND SPEEDS UP TO 110 MPH IN EXPOSURE CATEGORY B NOW EXCLUDES BUILDINGS LOCATED IN HURRICANE-PRONE REGIONS	2009	MODIFICATION			
2308.3.2	IT HAS BEEN CLARIFIED THAT THE CONNECTIONS RESISTING WIND AND SEISMIC LATERAL FORCES APPLY TO THE ENTIRE BRACED WALL LINE, NOT JUST THE BRACED WALL PANEL PORTION OF THE WALL	2009	MODIFICATION			
2308.6, 2308.12.8, 2308.12.9	THE PERMITTED USE OF STRAP ANCHORS IN LIEU OF ANCHOR BOLTS IN HIGH-SEISMIC REGIONS HAS BEEN CLARIFIED	2009	MADIFICATION			

2308.9.1	EXCEPT FOR TRIMMER AND CRIPPLE STUDS AT OPENINGS IN WALLS, WALL STUDS ARE NOW REQUIRED TO BE CONTINUOUS FROM A SUPPORT AT THE SOLE PLATE TO A SUPPORT AT THE TOP PLATE IN ORDER TO RESIST OUT-OF-PLANE LOADS PERPENDICULAR TO THE WALL	2009	MODIFICATION			
2308.12	TABLE 2308.12.4 HAS BEEN REVISED TO PROVIDE A MINIMUM PERCENTAGE RATHER THAN A MINIMUM LENGTH OF WALL BRACING FOR CONVENTIONALLY CONSTRUCTED BUILDINGS IN SEISMIC DESIGN CATEGORIES D AND E. NEW SECTION 2308.12.4.1 HAS BEEN ADDED TO CLARIFY THAT THE SUBSTITUTION OF ALTERNATE BRACED WALL PANELS IN BUILDINGS LOCATED IN SEISMIC DESIGN CATEGORIES D AND E IS PERMITTED. FOOTNOTE 'a' WAS ALSO MODIFIED SO THAT THE 2:1 HEIGHT-TO-WIDTH RATIO LIMITATION DOES NOT APPLY TO SUBSTITUTED ALTERNATE BRACED WALL PANELS.	2012	CLARIFICATION			
2406.1, 2406.4	THE HAZARDOUS LOCATIONS IDENTIFIED IN THE SAFETY GLAZING PROVISIONS HAVE BEEN REORGANIZED AND CLARIFIED IN ORDER TO PROVIDE BETTER CONSISTENCY BETWEEN THE IBC AND IRC	2012	MODIFICATION			
2406.1.1, 2406.2	SAFETY GLAZING MATERIALS MAY NOW COMPLY WITH ANSI Z97.1 RATHER THAN CPSC 16 CFR 1201 WHERE USED IN A LIMITED NUMBER OF SPECIFIED HAZARDOUS LOCATIONS					

2406.2	THE DEFAULT IMPACT TEST CRITERIA HAVE BEEN REVISED TO IMPOSE THE MORE RESTRICTIVE TEST METHODOLOGY. THE HIGHER IMPACT REQUIREMENTS WILL APPLY UNLESS THE TABLES IN SECTION 2406.2 ALLOW FOR A LOWER IMPACT TEST TO BE USED	2012	MODIFICATION			
2510.6	IN ORDER TO REDUCE THE LIKEHOOD OF MOISTURE GETTING INTO THE BUILDING, DETAILED REQUIREMENTS HAVE BEEN PROVIDED FOR THE INSTALLATION OF THE TWO LAYERS OF WEATHER-RESISTIVE BARRIERS THAT ARE REQUIRED BEHIND STUCCO-COVERED EXTERIOR WALLS	2012	MODIFICATION			
2603.4.1.14	THE USE OF ½ INCH WOOD STRUCTURAL PANELS INSTALLED ON THE WALKING SURFACE SIDE OF A FLOOR ASSEMBLY IS NOW PERMITTED AS AN ALTERNATIVE TO THE THERMAL BARRIER TYPICALLY REQUIRED WHERE FOAM PLASTIC INSULATION IS INSTALLED WITHIN A FLOOR ASSEMBLY	2012	ADDITION			
2603.7, 2603.8	THREE DIFFERENT OPTIONS FOR SEPARATING FOAM PLASTIC INSULATION USED IN PLENUM SPACES ARE NOW PROVIDED. THESE OPTIONS VARY IN RELATIONSHIP TO THE MAXIMUM PERMITTED FLAME-SPREAD AND SMOKE-DEVELOPED RATING INDEX	2012	MODIFICATION			
2603.10, 2603.10.1	THE SPECIFIC APPROVAL REQUIREMENTS NOW ENSURE THAT THE SMOKE DEVELOPMENT OF ALL ASSEMBLIES THAT CONTAIN FOAM PLASTIC IS EVALUATED, REGARDLESS OF THE TEST STANDARD USED	2012	MODIFICATION			

2610.3	THE DIMENSION THAT IS USED FOR DETERMINING THE MINIMUM SLOPE REQUIREMENTS OF A DOME SKYLIGHT HAS BEEN REVISED	2012	MODIFICATION			
2612, 202	FIBER-REINFORCED POLYMER INSTALLED ON AN EXTERIOR WALL MUST NOW BE A CLASS 'A' MATERIAL AND IS LIMITED TO 10 PERCENT OF THE EXTERIOR WALL AREA FOR ANY INDIVIDUAL ELEMENT OR GROUP OF NONSEPARATED ELEMENTS	2012	MODIFICATION			
2902.1.1	THE METHOD OF DETERMINING THE MINIMUM REQUIRED NUMBER OF PLUMBING FIXTURES HAS BEEN CLARIFIED FOR BUILDINGS THAT CONTAIN MULTIPLE OCCUPANCIES	2009	CLARIFICATION			
2902.2	WHERE SEPARATE SEX TOILET FACILITIES ARE REQUIRED AND ONLY ONE WATER CLOSET IS REQUIRED IN EACH FACILITY, TWO FAMILY OR ASSISTED-USE TOILET ROOMS MAY NOW BE PROVIDED AS AN ACCEPTABLE ALTERNATIVE	2012	MODIFICATION			
2902.3	PUBLIC TOILET FACILITIES ARE NO LONGER REQUIRED IN OPEN AND ENCLOSED PARKING GARAGES AND EMPLOYEE TOILET FACILITIES ARE NOT REQUIRED IN THOSE GARAGES THAT DO NOT HAVE PARKING ATTENDANTS	2012	MODIFICATION			
2902.3.5	IN OTHER THAN FAMILY OR ASSISTED-USE TOILET ROOMS, THE DOOR FROM A TOILET ROOM CAN NO LONGER BE LOCKABLE FROM THE INSIDE UNLESS THE TOILET ROOM IS A SINGLE-USER FACILITY	2012	ADDITION			

2902.5	DRINKING FOUNTAINS ARE NOW ALLOWED TO SERVE MULTIPLE TENANT SPACES PROVIDED THE FOUNTAINS ARE LOCATED WITHIN THE APPROPRIATE DISTANCES & AVAILABLE FOR THE USE OF THE OCCUPANTS	2012	CLARIFICATION			
2903	WATER CLOSET COMPARTMENT AND URINAL PRIVACY PROVISIONS ARE NOW ALSO LOCATED IN THE IBC FOR USABILITY PURPOSES	2009	ADDITION			
3002.4	WHERE AN ELEVATOR CAR IS REQUIRED TO ACCOMMODATE AN AMBULANCE STRETCHER, THE SIZE OF THE STRETCHER USED FOR THE MINIMUM CAR SIZE HAS BEEN MODIFIED TO MORE ACCURATELY IDENTIFY THE MINIMUM REQUIRED ELEVATOR CAR DIMENSIONS	2009	MODIFICATION			
3007	A FIRE SERVICE ACCESS ELEVATOR USING KEY FEATURES TO ASSIST FIREFIGHTERS IN ACCESS AND RESCUE OPERATIONS IS NOW REQUIRED IN HIGH-RISE BUILDINGS WITH AN OCCUPIED FLOOR MORE THAN 120 FEET ABOVE THE LOWEST LEVEL OF FIRE DEPARTMENT VEHICLE ACCESS	2009	ADDITION			
3007	MANY OF THE PROVISIONS ADDRESSING FIRE SERVICE ACCESS ELEVATORS HAVE NOW BEEN COORDINATED WITH THOSE APPLICABLE TO OCCUPANT EVACUATION ELEVATORS TO ENSURE THAT THE FIRE SERVICE ACCESS ELEVATORS ARE ABLE TO CONTINUE TO FUNCTION AND SERVE THEIR INTENDED PURPOSE DURING AN EMERGENCY	2012	MODIFICATION			

3008	SPECIFIC PROVISIONS HAVE BEEN ADDED TO ADDRESS THE USE OF PASSENGER ELEVATORS FOR OCCUPANT EVACUATION PURPOSES	2009	ADDITION			
3008	THE PROVISIONS ADDRESSING OCCUPANT EVACUATION ELEVATORS ARE NOW MORE CLOSELY COORDINATED WITH THOSE REGULATING FIRE SERVICE ACCESS ELEVATORS	2012	MODIFICATION			
3108	THE REFERENCED STANDARD FOR STRUCTURAL DESIGN OF ANTENNA SUPPORTING TOWERS, TIA 222-G, CONTAINS EXEMPTIONS FOR SEISMIC DESIGN THAT ARE NOT CONSISTENT WITH THE REQUIREMENTS OF IBC CHAPTER 16 AND ASCE 7, THEREFORE SECTION 3108.1 HAS BEEN MODIFIED SO THAT THE EXEMPTIONS ARE NOT APPLICABLE	2012	MODIFICATION			
3302.3, 3303.7, 3313	CONSTRUCTION PROTECTION REQUIREMENTS OF THE IFC HAVE BEEN INCORPORATED ITO THE IBC TO ENSURE THEY ARE NOT OVERLOOKED	2012	ADDITION			
3401.3	IT HAS NOW BEEN SPECIFICALLY ESTABLISHED THAT THE EXISTING BUILDING PROVISIONS OF CHAPTER 34 ARE VIEWED AS SPECIFIC PROVISIONS AND THEREFORE TAKE PRECEDENCE OVER REQUIREMENTS IN OTHER CODES	2012	MODIFICATION			
3401.4	THE USE OF THE INTERNATIONAL EXISTING BUILDING CODE FOR REGULATING EXISTING BUILDINGS UNDERGOING REPAIR, ALTERATIONS, ADDITIONS, OR CHANGE OF OCCUPANCY IS NOW SPECIFICALLY PERMITTED AS AN ALTERNATIVE TO CHAPTER 34 OF THE IBC	2009	ADDITION			

